

LOW COST

READILY AVAILABLE

QUICK SAMPLES

TECH SUPPORT

Technical Specs:

- 750 Minimum Mating Cycles
- Voltage: 125VAC
- Current: 1.5A
- DWV: 1.5kVAC (contact - shield)
- Extended Operating Temperature -40°C to +85°C
- UL94V-0 Flammability Rating

HALO Electronics
2880 Lakeside Drive
Suite 116
Santa Clara, CA 95054

8P8C Modular Shielded RJ45



Single Port RJ45

- 6u", 30u", or 50u" Gold Plating on Contacts
- Choice of LED colors
- HCJ11 (Tab-Down)
- HCJT1 (Tab-Up)
- HCJV1 (Vertical)
- Alternate Footprints Available

Ganged RJ45



- 6u", 30u", or 50u" Gold Plating on Contacts
- Choice of LED colors
- HCJT2 (1x2 Tab-Up)
- HCJT4 (1x4 Tab-Up)
- Alternate Footprints Available

Stacked and Ganged RJ45



- 6u", 30u", or 50u" Gold Plating on Contacts
- Choice of LED colors
- HCJ21 (2x1)
- HCJ22 (2x2)
- HCJ24 (2x4)
- HCJ26 (2x6)

Download Datasheets:

<https://www.haloelectronics.com/products/connectors/>

Additional Modular Connectors Available:

- Unshielded/Shielded (6P6C, 8P8C, 10P10C)
- RJ45/USB Combo

For more information please contact your local manufacturers representative, regional manager, or HALO direct at:

info@haloelectronics.com
(650) 903-3800